

Village Marine LTM-500 Modular Watermaker



For commercial and leisure applications.

79L/Hour (1,896 L/Day)

Standard Features:

- 220V 50Hz Single Phase (8 amp)
- Powder coated mounting brackets
- 5 micron cleanable prefilter
- Control manifold pressure regulator ensures consistent pressure adjustments and prevents over or under pressurisation of the unit. Adjustable to allow operation in brackish or fresh water
- High quality 2.5" diameter spiral wound TFC reverse osmosis membrane
- · Magnetic drive boost pump
- Stainless steel glycerine filled low and high pressure gauges
- High pressure plunger pump with 316 stainless steel head
- Manual freshwater flush valve and carbon filter to remove chlorine from flush water.
- Acrylic flowmeter to monitor fresh water production

The LTM 500 offers high quality Parker Village Marine engineered components with straightforward manual operation.

Driven by AC motors (from genset power) the modular configuration comes in ready to mount modules for flexible installation options.

Integral to every LTM 500 unit is a control manifold which includes a pressure regulation valve, high pressure gauge, product flow meter and manual freshwater diversion valve.

Options:

Auto fresh water flush with repeat timer to optimally maintain the system (refer to items in blue on drawing on following page).

Membrane cleaning and preserving cartridges for simple membrane cleaning or preserving without hoses and buckets.



Unit 18, 17 Rivergate Place Murarrie QLD 4172

T +61 07 3640 5600 F +61 07 3640 5699

www.tmq.com.au

LTM-500 PLUMBING DIAGRAM FOR INSTALLATION WITH SMART FLUSH SYSTEM

